

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8757)

Set a Fir post, 4 ft. long, 4" sq., 20" in the ground for the corner to secs. 17, 18, 19 and 20 marked T32S R7W S17 on the NE.; S20 on SE.; S19 on SW.; and S18 on NW.; also three notches on N. and 5 notches on East angles of same, from which

- A Laurel 8" dia., bears N.35°E., 53 lks. mkd. T32S R7W S17 BT.
- A Laurel 8" dia., bears S.70°E., 45 lks. mkd. T32S R7W S20 BT.
- A Fir 48" dia., bears S.37°W., 90 lks. mkd. T32S R7W S19 BT.
- A Fir 36" dia., bears N.52°W., 146 lks. mkd. T32S R7W S18 BT.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records Vol. 42 Page(s) 16499-50)

The Sec. cor., determined from the remains of the original bearing trees:

- A root hole bears N.45°E., 53 lks. dist. (Rec. N.35°E.)
- A root hole bears S.37°W., 90 lks. dist. with a down and decayed Fir alongside, 48" dia., no marks visible.
- A Fir 45" dia., bears N.55°W., 135 lks. dist., with illegible scribe marks visible on burned bark blaze. (Rec. N.52°W., 146 lks.)

and the remains of bearing trees of which I have no record:

- A Fir 18" dia., bears N.17°E., 58 lks. dist., with scribe marks 2968 BT visible on partially healed blaze.
- A sawed Fir stump 14" dia., bears S.2°E., 60½ lks. dist., with scribe marks BT visible on open blaze, with a down Fir alongside, 14" dia., with scribe marks 2968 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 32 S R 7 W
S 18 | S 17
S 19 | S 20
1978

from which new bearing trees

- A Fir 27" dia., bears N.31½°E., 52 lks. dist., mkd. T32S R7W S17 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

A Fir 17" dia. bears S.80¼°E. 69 lks. mkd. T32S R7W S20 BT
A Fir 12" dia. bears S.50½°W. 50 lks. mkd. T32S R7W S19 BT
A Fir 10" dia. bears N.38½°W. 23 lks. mkd. T32S R7W S18 BT

Jerry Estabrook - Bruce Webster 4/2003 - C.S. File 65/45-22

Condition Report

Found - 3¼" BLM brass cap on 2" galv. iron pipe, 0.2 above grade.
45" fir bears N.55°W., 86.7 ft. (89.1 ft) BLM 1978
19" fir with healed face bears N.17°E., 42.3 ft. (38.3 ft.)
36" fir stump bears S.2°E., 38.4 ft. (39.9 ft)
28" fir with healed face bears N.31°30'E., 34.9 ft. (34.3 ft.) BLM 1978
19" fir bears S.80°15'E., 45.5 ft. (BLM 1978)
15" fir with healed face bears S.50°30'W., 33 ft. (BLM 1978)
13" fir bears N.38°30'W., 15.2 ft. (BLM 1978)

BLM Dependent resurvey by Stephan L. Barott, Cadastral Surveyor (Forest Service, USDA) under Group #1995, surveyed April/Nov. 2002 - (DCSO records Vol. 54 Page(s) 21163-4)

The cor. of secs. 17, 18, 19, & 20, monumented with an iron post, 2½" dia., firmly set, projecting 8" above the ground, with brass cap (properly) mkd., from which the remains of the original bearing trees
A root hole, bears S.37°W., 59.4 ft. with down & decayed fir alongside, size indeterminate, with no scribe marks visible.
A fir, 46" dia., bears N.55°W., 86.8 ft., with axe marks visible on burned bark blaze. (Record 89.1 ft.) and a bearing tree mkd. by person(s) unknown reported by Roseberry and Aanrud
A fir, 20" dia., bears N.14¾°E., 42.2 ft., with a healed double blaze. (Record, N.17°E., 38.3 ft.) and bearing trees mkd. by Roseberry and Aanrud
A fir, 28" dia., bears N.28½°E., 34.3 ft., with a healed blaze. (Record N.31½°E.)
A fir, 17" dia., bears S.80¾°E., 45.5 ft., with a healed blaze.
A fir, 15" dia. bears S.50½°W. 33.0 ft with healed blaze
A fir, 13" dia. bears N.38½°W. 15.2 ft with healed blaze