

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO recs Vol. 21 Page 8759)</p> <p>-----</p> <p>Set a Laurel post 4 ft. long, 4" sq., 24" in the ground marked ¼ S on W. side for the ¼ sec. cor., from which: A Laurel 5" dia., bears N.63°E., 15 lks. mkd. ¼ S BT. A Live Oak 5" dia., bears S.35°W., 14 lks. mkd. ¼ S BT.</p>
<p>BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records Vol. 42 Page(s) 16502-03)</p> <p>-----</p> <p>Point for the ¼ cor., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked T 32 S R 7 W 1/4 S 18*S 17 1978</p> <p>from which A Fir 6" dia., bears N.37½°E., 48 lks., mkd. ¼ S17 BT. A Fir 6" dia., bears N.53°W., 22½ lks., mkd. ¼ S18 BT.</p>
<p>Jerry Estabrook - Bruce Webster 4/2003 - C.S. File 65/45-23</p> <p>-----</p> <p>Found - 3¼ BLM brass cap on 2½" galv. iron pipe. (BLM 1978) 7" fir with healed face bears N.37°30'E., 31.7 ft. (BLM 1978) 7" fir with healed face bears N.53°W. 14.9 ft (BLM 1978)</p> <p>New - 25" sugar pine scribed (T32S R7W S18 E¼ BT) bears S.5°W., 18.9 ft. to side center. 18" D.Fir scribed (T32S R7W S17 W¼ BT) bears S.75°E., 35.2 ft. to side center.</p> <p>Note - Approx. 0.3 miles in on spur 32-7-17.2. Corner falls approx. 125 ft. South of said spur on South facing slope.</p>
<p>Ron Quimby - 10/2013 - C.S. File 65/80-30</p> <p>-----</p> <p>Found - BLM brass cap A 10" D.Fir N.37°E., 31.7 ft. healed face A 10" D.Fir N.53°W., 14.9 ft. healed face. A 28" Pine S.5°W., 18.9 ft. healed face. A 20" D.Fir S.75°E., 35.2 ft. healed face.</p> <p>New - Set alum. post 2.0 north & south. Re-tag trees</p> <p>Note - See C.S. 65/45-23. Area burnt 7/2013</p>