

PRIMARY CORNER DESCRIPTION Sec Cor for 7, 8, 17 and 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8759-60)

Marked a Fir tree, 8" dia., for the corner to secs. 7, 8, 17 and 18 marked T32SR7W S8 on NE.; S17 on SE.; S18 on SW.; S7 on NW. faces, with 4 notches on the S. and 5 notches on the E. angles, from which:

- A Fir 6" dia., bears N.30°E., 16 lks. mkd. T32S R7W S8 BT
- A Fir 6" dia., bears S.30°E., 21 lks. mkd. T32S R7W S17 BT
- A Laurel 8" dia. bears S.40°W., 12 lks mkd T32S R7W S18 BT
- A Laurel 10" dia. bears N.60°W., 48 lks mkd T32S R7W S7 BT

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records Vol. 42 Page(s) 16503)

The Sec. cor., determined from the remains of the original corner tree, a root hole with a down Fir alongside, 18" dia., with scribe marks S17 visible on opened SE. blaze and illegible scribe marks visible on opened SW. blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked

T 32 S R 7 W
S 7*S 8
S 18*S 17
1978

from which

- A Fir 9" dia., bears N.32½°E., 48 lks. mkd. T32S R7W S8 BT
- A Fir 16" dia., bears S.34°E., 54½ lks mkd T32S R7W S17 BT
- A Fir 18" dia., bears S.59°W. 93½ lks mkd. T32S R7W S18 BT
- A Fir 7" dia., bears N.56½°W., 25½ lks. mkd T32S R7W S7 BT

Ron Quimby - 10/2013 - C.S. File 65/80-31

Found - 1978 BLM brass cap (properly mkd)

- 14" Fir N.32°E., 31.7 healed face.
- 20" fir S.34°E., 36.0 healed face.
- 24" fir S. 59°W., 61.7 healed face.
- 12" fir N.56°W., 16.8 healed face.

New - Set alum. post 2.0 west and 2.0 south. Re-tag trees.

Note - Area burnt 7/2013