

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8762)

Set a Laurel post 4 ft. long, 4" sq., 24" in the ground, marked ¼ S on W. side for the ¼ sec. cor., from which
A Laurel 12" dia., bears S.72°E., 18 lks. mkd. ¼ S BT.
A Laurel 6" dia., bears S.50°W., 56 lks. mkd. ¼ S BT.

Reported as: Not found 2 small laurels in heavily logged area. Clear cut, 3/18/1967 C.S. 54/36-111 & 2 small laurels, area logged good N-S blazed line 4/2/1968 C.S. 54/36-115 both by JP DCSO (added 10/12/2016)

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records Vol. 42 Page(s) 16506)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked
T 32 S R 7 W
1/4
S 7 | S 8
1978

from which
A Fir 13" dia., bears S.34°E., 60½ lks. mkd. ¼ S8 BT.
A Fir 12" dia., bears S.39°W., 79½ lks. mkd. ¼ S7 BT.

Survey by Max Hull, L.S. #901 - For: Gregory Forest Products August 1989 - C.S. File 63/24 and M 108-69

Found - 1978 BLM brass cap, out of position, N.72°43'32"W., 7.58 ft.

Set, by proportion, a 5/8" x 30" Iron rod with cap mkd. "Hull RS 901".

Used BLM BTs:

15" Fir S.26°E., 34.35 ft. B.H.
14" Fir S.46°W., 55.72 ft. B.H.