

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for secs. 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Pg 8762)

Set a Fir post, 4 ft. long, 4" sq., for the cor. to secs. 5, 6, 7 and 8 marked T32S R7W S5 on NE.; S8 on SE.; S7 on SW.; and S6 on NW. faces. Also 5 notches on S. and 5 on E. angles of same, from which:

- A Pine 12" dia., bears N.68°E., 32 lks. mkd. T32S R7W S5 BT.
- A Pine 15" dia., bears S.52°E., 26 lks. mkd. T32S R7W S8 BT.
- A Pine 12" dia., bears S.15°W., 10 lks. mkd. T32S R7W S7 BT.
- A Laurel 10" dia., bears N.62°W., 38 lks. mkd. T32S R7W S6 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - April 1968 - C.S. File 54/36

- Found - Orig. 12" now 21" S.Pine N.68°E., 21.1 ft., shows scar.
Orig. 12" now 20" S.Pine, face burnt, S.15°W., 6.6 ft.
Orig. 15" now 26" S.Pine S.52°E., 17.2 ft., tree opened shows scribe "W" and parts of other marks.
Orig. 10" now 19" Laurel N.62°W., 25.1 ft. shows scar.

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 7 W
S 6 | S 5
S 7 | S 8
1968

- New BTs - reblazed and rescribed:
21" S.Pine N.68°E., 21.1 ft. mkd. T32S R7W S5 CS BT
20" S.Pine S.15°W., 6.6 ft. mkd. T32S R7W S7 CS BT.
26" S.Pine S.52°E., 17.2 ft. mkd. T32S R7W S8 CS BT.
19" Laurel N.62°W., 25.1 ft. mkd. T32S R7W S6 CS BT.

Fd. and Used in BLM resurvey by Roseberry and Aanrud, under Group #'s 350 and 960, surveyed Aug/Sept. 1978 - (DCSO records, Vol. 42 Pages 16505-07)

Cor. Fd. and used in BLM resurvey by Jelley, under Group #1086, surveyed April/June 1982 - (DCSO records, Vol. 46 Page 17565)

Fd. OK, by Max Hull, Sept. 1989, C.S. File 63/24 and M 108-69