

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 209100

PRIMARY CORNER DESCRIPTION C C for Secs. 5 and 6 only, T33-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 21 Page(s) 9061)

-----  
I set a granite stone, 18 x 12 x 6 ins., 12" in the ground for closing corner of secs. 5 and 6 marked C C on S.; with 5 grooves on E.; and 1 groove on W. faces, from which  
A Fir 15" dia., bears S.57°W., 100 lks. dist., mkd. T33S R7W S6 BT.  
A Sugar Pine 32" dia., bears S.81°E., 78 lks. dist., mkd. T33S R7W S5 BT.

Douglas Co. Surveyors Office - Frank Jones & crew - May 27, 1968 - C.S. File 54/36-184

-----  
Found - 1" I.Pipe 24" long at corner. (No trace of corner stone)  
15" D.Fir now 24" snag, S.57°W., 66.0 ft. shows bark scribing of BT  
32" Sugar Pine now 42", S.81°E., 51.5 ft. shows a scar.

Set Brass cap at cor. mkd: County Surveyors Office  
T 32 S R7W CC S 32  
T 33 S S 6 | S 5  
1968

Rescribed: 42" S.Pine S.81°E., 51.5 ft. scribed T33S R7W S5 CC CS BT.

New BT - 10" D.Fir N.69°W., 71.0 ft. mkd. T32S R7W S32 CS BT.  
There were no other trees for scribing.

This corner lies 603.9 ft. East of S.C. of S31|S32, T32-7