

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION S 1/4 Cor Sec 32 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8704-05)

Set a Laurel post, 4 ft. long, 4" sq., 18" in the ground, for the ¼ sec. cor. mkd. S C ¼ S on N. side, from which
A Fir 26" dia., bears S.20°W., 20 lks. dist., mkd. S C ¼ S BT.
A Cedar 15" dia., bears N.15°W., 70 lks. dist., mkd. S C ¼ S BT.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 21 Page(s) 8766-67)

The ¼ sec. cor. which having disappeared, I replace by setting a Cedar Post, 3 ft. long, 3" sq., 24" in the ground, for standard ¼ sec. cor. mkd. S C ¼ S32 on N. face, and 5 on S. face, from which,
An Alder 4" dia., bears N.28°W., 21 lks. dist., mkd. S C ¼ S32 BT. New BT.
A Fir 30" dia., bears S.20°W., 20 lks. dist., mkd. S C ¼ S BT. Orig. BT.
This corner stands 250 ft. above creek, 10 lks. wide. A cabin stands S. of Cor., 33 lks.

Survey by Norman D. Price - For: Dollar and Patterson Lumber Co. - May 1956 - C.S. File 42/143-3

Determined at the record bearing and distance from the extant original bearing tree.
Set an iron pipe, 3 ft. long, 1½" dia., 28" in the ground, mkd. RS33., from which the original bearing tree:
A D.Fir 36" dia., bears S.20°W., 20 lks. dist., mkd. on bark SC ¼ S BT.
and a new bearing tree:
An Incense Cedar 10" dia., bears N.75°E., 28 lks. dist., mkd. SC ¼ S32 RS33 BT.

Fd. OK, DCSO, J. Powell, May 1, 1968 C.S. File 54/36-155