

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8753)

Set a Laurel post 4 ft. long, 4" sq., 20" in the ground for the ¼ sec. cor. mkd. ¼ S on N. side, from which:
A laurel , 5" dia., bears S.40°W., 10 lks., mkd: ¼ S BT.
A laurel, 5" dia., bears N.38°W., 54 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John Powell & crew - 12/1967 - C.S. File 54/36-133

(Reported as) Not Found.
(Two small laurels)

Daniel Baker - For: Weyerhaeuser Co. - 11/2017 - M174-4

Set - 5/8"x36" rebar with 2½" aluminum cap, mkd:
T32S R7W
¼ $\frac{S\ 29}{S\ 32}$
PLS 1978
2017
57" Pine, N.19°E., 55.8' to nail side/center-scribed
"¼ S29 BT"
6" PINE, S.77°E., 8.5' to nail side/center-scribed
"¼ S32 BT
5/8"x30" rebar with red plastic cap "REF. MON. PLS 1978" bears S.10°46'16"W., 33.25'
5/8"x30" rebar with red plastic cap "REF. MON. PLS 1978" N.59°06'00"W., 52.79'
5 FT metal post alongside corner.