

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8758)

Set a Laurel post, 4 ft. long, 4" sq., 20" in the ground, marked $\frac{1}{4}$ S on N. side for the $\frac{1}{4}$ sec. cor., from which
A Laurel 6" dia., bears S.62°W., 27 lks. mkd. $\frac{1}{4}$ S BT.
A Fir 20" dia., bears N.45°E., 19 lks. mkd. $\frac{1}{4}$ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - November 1967 - C.S. File 54/36-149

Found - 20" now 28" D.Fir N.45°E., 12.5 ft. bark scribe $\frac{1}{4}$
No trace of other bearing tree.

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 7 W
 $\frac{1}{4}$ $\frac{S}{S}$ $\frac{17}{20}$
1967

Rescribe-28" D.Fir N.45°E., 12.5 ft. mkd. $\frac{1}{4}$ S17 CS BT.
New BT - 10" D.Fir S.12 $\frac{1}{2}$ °E., 22.4 ft. mkd. $\frac{1}{4}$ S20 CS BT.
This corner lies on steep East slope 200 ft. W. of creek.

BLM Dependent resurvey by Stephan L. Barott, Cadastral Surveyor (Forest Service, USDA) under Group #1995, surveyed April/Nov. 2002 - (DCSO records Vol. 54 Page(s) 21162-3)

The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, perpetuated by the Douglas County Surveyor's Office in 1967, monumented with iron pipe, 1 $\frac{1}{4}$ " dia., firmly set, projecting 16" above the ground, with brass cap (properly) mkd.
from which the remaining original bearing tree
A fir, 29" dia., bears N.42°E., 12.9 ft., with a healed double blaze; rescribed by the County Surveyor's Office in 1967. (Record, N.45°E., 12.5 ft.)
and a bearing tree mkd. by the County Surveyor's Office
A fir, 13" dia., bears S.14°W., 22.2 ft., with a healed double blaze.