

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8760)

-----  
Set a Laurel post 4 ft. long, 4" sq., 24" in the ground, mkd. 1/4 S on N. side for the 1/4 sec. cor., from which:  
A Laurel 5" dia., bears North 8 lks. mkd. 1/4 S BT.  
A Laurel 5" dia., bears S.10°W., 7 lks. mkd. 1/4 S BT.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records Vol. 42 Page(s) 16504)

-----  
Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked T 32 S R 7 W

1/4  $\frac{S \ 8}{S \ 17}$   
1978

from which  
A Fir 7" dia., bears N.32°W., 53 lks. mkd. 1/4 S8 BT.  
A double Fir 18" dia., bears S.36°E., 29 lks. mkd. 1/4 S17 BT.