

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8763)

Marked a Pine tree, 16" dia., with blaze and ¼ S on N., also 2 notches on E. and W. sides, for the ¼ sec. cor., from which
A Sugar Pine 60" dia., bears North, 56 lks. mkd. ¼ S BT.
A Sugar Pine 50" dia., bears S.50°E., 47 lks. mkd. ¼ S BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1086, surveyed April/June 1982 - (DCSO records Vol. 46 Page(s) 17564-65)

The ¼ sec. cor., monumented with the remains of the original corner tree; a sawed Pine stump, 24" dia., no marks visible, from which the remains of the original bearing trees:
A Sugar Pine 53" dia., bears North, 59 lks. dist., axe marks visible on bark. (Rec. 56 lks.)
A sawed Sugar Pine stump, 54" dia., bears S.50°E., 52 lks. dist., no marks visible. (Rec. 47 lks.)
and a new bearing tree and reference monument:
A Fir 5" dia., bears S.76°E., 23 lks. mkd. ¼ S8 BT.
An aluminum post, 28" long, 2½" dia., set 24" in the ground, for a reference monument, bears N.40°W., 15 lks. dist., with aluminum cap mkd. RM 1/4 S5 1982 and an arrow pointing to the corner.