

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8743)

Set a Laurel post, 4 ft. long, 4" sq., 20" in the ground, marked ¼ S on W. side for the ¼ sec. cor., from which
A Laurel 12" dia., bears S.31°E., 19 lks. mkd. ¼ S BT.
A Laurel 10" dia., bears N.54°W., 19 lks. mkd. ¼ S BT.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - March/Aug. 1954 - C.S. File 41/301

Determined at the record bearing and distance from the original SE BT.

At the corner point

Set an Iron pipe 3 ft. long, 1½" dia., 28" in the ground, mkd. RS33; from which an original bearing tree

A Madrona 17" dia., bears S.31°E., 19 lks. dist., with the scribe marks ¼ S visible.

Find no evidence of the original NW BT.

New bearing trees:

A Madrona 9" dia., bears S.85°E., 48 lks. dist., mkd. ¼ S33 RS33 BT.

An Incense Cedar 19" dia., bears N.70°W., 49 lks. dist., mkd. ¼ S32 RS33 BT.

Fd. OK, DCSO, J. Powell, Dec. 13, 1967, C.S. File 54/36-116
Fd OK by R. Templin, July 1995 - M122-53

Ron Quimby - Crew: N. Fromdahl & D. Manring - 9/2014 - C.S. File 65/86-23

Found - 1½" I. Pipe.
13" Madrona S.85°E., 31.7 hollow scar
29" Madrona S.31°E., 12.5 hollow scar
40" I.Cedar N.70°W., 32.3 ft good scar

New - 6" Fir N.67°E., 10.6 ft. scribed ¼ S33 BT.

6" Fir S.58°W., 22.6 ft. scribed ¼ S32 BT.

Note - Area burnt 8/2013.
Compass decl. 15½°E.