

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Pg 8743)

Set a Laurel post, 4 ft. long, 4" sq., 22" in the ground for the corner to secs. 28, 29, 32 and 33 marked T32S R7W S28 on NE.; S33 on SE.; S32 on SW.; and S29 on the NW. side. Also 1 notch on S. and 4 notches on E. angle of same, from which

A Fir 18" dia., bears N.18°E., 88 lks mkd T32S R7W S28 BT
 A Laurel 4" dia., bears S.40°E., 9 lks mkd T32S R7W S33 BT
 A Laurel 4" dia. bears S.40°W., 38 lks mkd T32S R7W S32 BT
 A Fir 30" dia., bears N.54°W., 130 lks mkd T32S R7W S29 BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - Dec. 1967 - C.S. File 54/36-132

Found - 18" now 51" D.Fir N.18°E., 58.1 ft., faint bark scribe "B", other marks not legible. (Orig.)
 Orig. 30" now 51" D.Fir N.54°W., 85.8 ft., no scribing visible.

No trace of 2-4" Laurels (Orig.) SE and SW.

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 7 W	
S 29	S 28
S 32	S 33
1967	

New BTs -10" Laurel S.26°E., 2.7 ft. mkd. T32S R7W S33 CS BT.
 14" Laurel S.9°W., 20.0 ft. mkd. T32S R7W S32 CS BT.
 9" Laurel N.44°W., 12.8 ft. mkd. T32S R7W S29 CS BT.
 13" Laurel N.45°E., 33.2 ft. mkd. T32S R7W S28 CS BT

This corner hits call of 495.0 ft. N. of top of ridge good.

Fd. OK, M. Smalley, July 1993, M 117-48

Ron Quimby - Crew: N. Fromdahl & D. Manring - 9/2014 - C.S. File 65/86-24

Condition report only

Found - DCSO brass cap

65" D.Fir N.18°E., 58.1' bark scribe.
 15" Madrona N.45°E., 33.2 ft. good scar.
 13" madrona S.26°E., 2.7 ft. vis. scribe.
 15" madrona S.9°W., 20.0 ft. vis. scribe.
 65" Fir N.54°W., 85.8 ft. bark scribe.
 11" Madrone N.44°W., 12.8 ft. vis. scribe.

Note - Area burnt 8/2013
 Compass decl. 15½°E.

continued next page

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Daniel Baker - For: Weyerhaeuser Co. - 11/2017 - M174-4

Found - 2½" Douglas CO. Brass cap "1967"
65" Fir, N.18°E, 58.1' to center-original BT (bark scribed)
15" Madrone, N.45°E., 33.2' to center - 1967 Douglas Co. BT
13" Madrone, S.26 E, 2.7' to center - 1967 Douglas Co. BT (scribe visible)
15" Madrone, S.9°W., 20.0' to center - 1967 Douglas Co. BT (scribe visible)
65" Fir, N.54°W., 85.8' to center - original BT (bark scribed)
11" Madrone, N.44°W., 12.8' to center - 1967 Douglas Co. BT (scribe visible)

Bearings and distances to BTs are record per rec.
Set 5 foot metal post alongside corner