

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8744-45)

Set a Fir post, 4 ft. long, 4" sq., 22" in the ground, marked ¼ S on W. side for the ¼ sec. cor., from which
A Chinquapin 10" dia., bears S.78°E., 58 lks. mkd. ¼ S BT.
A Fir 60" dia., bears N.28°W., 23 lks. mkd. ¼ S BT.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - Dec. 1954/May 1956 - C.S. File 42/142

Corner determined at the record bearing and distance from the only extant bearing tree.
Set an Iron pipe 3 ft. long, 1½" dia., 28" in the ground, mkd. RS33; from which the only extant orig. bearing tree:
A Chinquapin 15" dia., bears S.78°E., 58 lks. dist., mkd. on bark ¼ S BT.
And new bearing trees:
A Chinquapin 8" dia., bears S.72°E., 11 lks. dist., mkd. ¼ S28 RS33 BT.
A Chinquapin 12" dia., bears N.72°W., 6 lks. dist., mkd. ¼ S29 RS33 BT.

Fd. OK, DCSO, J.Powell, Nov. 30, 1967 - C.S. File 54/36-156

Survey by Mark Smalley, L.S. #2354 - For: Roseburg Resources July 1993 - M 117-48

Found - 1½" Iron pipe.
14" Chinquapin N.72°W., 4.0 ft., scribe visible.
10" Chinquapin S.72°E., 7.3 ft., scribe visible.
New BTs - 9" Chinquapin N.44°E., 15.6 ft. "¼ S28 BT".
8" Fir S.14°W., 28.0 ft. "¼ S29 BT".