

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8745)

Set Oak post 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 20, 21, 28 and 29 marked T32S R7W S21 on NE.; S28 on SE.; S29 on SW.; and S20 on NW. faces, also 2 notches on S. and 5 notches on E. faces, from which
A Pine 8" dia., bears N.20°E., 26 lks. mkd. T32S R7W S21 BT.
A Laurel 10" dia., bears S.10°E., 32 lks. mkd. T32S R7W S28 BT.
A Pine 36" dia., bears S.25°W., 90 lks. mkd. T32S R7W S29 BT.
A Pine 7" dia., bears N.53°W., 21 lks. mkd. T32S R7W S20 BT.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - Dec. 1954/May 1956 - C.S. File 42/142

Determined at the record bearing and distance from each extant original bearing tree.
Set an Iron pipe 3 ft. long, 2" dia., 28" in the ground, mkd. RS33, from which the extant original bearing trees:
A Madrona 18" dia., bears S.10°E., 37 lks. dist., badly burnt.
A dead Yellow Pine 40" dia., bears S.25°W., 84 lks. dist., with partial scribe marks on bark and lower blaze healed.
And new bearing trees:
A Yellow Pine 30" dia., bears N.53°E., 94 lks. dist., mkd. T32S R7W S21 RS33 BT.
A Madrona 5" dia., bears S.74°E., 26 lks. dist., mkd. on bark T32S R7W S28 RS33 BT.
A Yellow Pine 24" dia., bears N.62°W., 101 lks. dist., mkd. T32S R7W S20 RS33 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - November 1967 - C.S. File 54/36-148

Found - Orig. 18" Laurel, now down, S.10°E., 24.4 ft.
Orig. 40" Pine, now stob, S.25°W., 55.4 ft., tree opened, scribe marks visible.
2" Iron pipe at section corner.
30" Pine now 30", N.53°E., 62.0 ft. scribe visible, T32S R7W S21 RS33 BT.
5" now 7" Laurel S.74°E., 17.2 ft., bark scribe visible. (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. cor. for 20, 21, 28 and 29

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

24" Pine now 7 ft. stob, N.62°W., 66.7 ft. scribe visible "BT".
 2" I.Pipe at sec. cor.
 New BTs -6" Laurel N.79°W., 8.1 ft. mkd. T32S R7W S20 CS BT.
 6" Laurel S.67°W., 15.8 ft. mkd. T32S R7W S29 CS BT

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records Vol. 42 Page(s) 16496-97)

 The Sec. cor., perpetuated and recorded by Price in 1956, and further perpetuated and recorded by Powell in 1967, monumented with a galv. iron pipe, 2" dia., firmly set, projecting 8" above ground, from which the remains of original bearing trees:

A root hole bears S.10°E., 37 lks. dist. with a down burned and decayed Madrone alongside, 18" dia., no marks visible. (Rec. 32 lks.)

A sawed and decayed Ponderosa Pine stump 40" dia., bears S.25°W., 84 lks. dist., with illegible scribe marks visible on bark. (Rec. 90 lks.)

and the remains of bearing trees mkd. by Price:

A Ponderosa Pine 30" dia., bears N.53°E., 94 lks. dist., with scribe marks T32S R7W S21 RS33 BT visible on partially healed blaze.

A decayed Pine stump 24" dia., bears N.62°W., 101 lks. dist., with scribe marks BT visible on detached blaze.

and the remains of bearing trees mkd. by Powell:

A Madrone stump 8" dia., bears S.66½°W., 24 lks. dist., with scribe marks T32S R7W S29 CS BT visible on partially healed double blaze.

A Madrone 7" dia., bears N.78°W., 12 lks. dist., with scribe marks T32S R7W S20 CS BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T	32	S	R	7	W
	S	20		S	21
	S	29		S	28
					1978

from which new bearing trees:

A Fir 6" dia., bears S.8¼°E., 79 lks. dist., mkd. T32S R7W S28 BT.

A Fir 6" dia., bears S.60½°W., 39½ lks. dist., mkd. T32S R7W S29 BT.

Reset Iron pipe alongside iron post.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by Stephan L. Barott, Cadastral Surveyor (Forest Service, USDA) under Group #1995, surveyed April/Nov. 2002 - (DCSO records Vol. 54 Page(s) 21158-60)

The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd.,

from which the remains of the original bearing trees
A madrone stump, 10" dia., bears S.10°E., 22.1 ft., with no scribe marks visible. (Record 24.4 ft.)

A pine stump, size indeterminate, bears S.25°W., 55.4 ft., with fragmentary scribe marks visible on a detached face lying loose on the ground alongside.

and the remains of BTs mkd. by Price, reported by Roseberry & Aanrud

A pine snag, 27" dia., bears N.53°E., 62.0 ft., with scribe marks RS 33 BT visible on partially opened blaze.

A madrone stump, 12" dia., bears S.74°E., 16.1 ft., with no scribe marks visible. (Record, S.66½°W.)

A pine stump, size indeterminate, bears N.62°W., 66.7 ft., with no scribe marks visible.

and the remains of bearing trees mkd. by the County Surveyors Office, reported by Roseberry and Aanrud

A root hole, bears S.66½°W., 15.8 ft.

A madrone, 10" dia., bears N.78°W., 7.9 ft., with a healed blaze.

and bearing trees mkd. by Roseberry and Aanrud

A fir, 14" dia., bears S.8¼°E., 52.1 ft. with a healed blaze.

A fir, 16" dia., bears S.60½°W., 26.1 ft., with fragmentary scribe marks visible on an opened blaze.

and bearing trees marked by person(s) unknown

A fir, 11" dia., bears N.49½°E., 18.6 ft., with scribe mark 7 visible on partially opened blaze and "Roseburg Lumber Co." BT tag.

A fir, 16" dia., bears S.28½°E., 28.2 ft., with a healed blaze and "Roseburg Lumber Co." BT tag.