

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8746)

Set a Pine post 4 ft. long, 4" sq., 24" in the ground, for the ¼ sec. cor., mkd. ¼ S on W. side, from which:
A Pine 10" dia., bears S.80°E., 48 lks. mkd. ¼ S BT.
A Pine 9" dia., bears S.78°W., 78 lks. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - November 1967 - C.S. File 54/36-147

Found - Orig. 9" now 30" Pine S.78°W., 51.5 ft., opened for scribe "¼".

Orig. 10" Pine, now down and burnt, S.80°E., 24.7 ft. (Rec. 31.7 ft.) This tree all but burnt up.

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 7 W

¼ S20|S21

1967

New BTs -8" D.Fir N.81°W., 13.4 ft. mkd. ¼ S20 CS BT.

12" D.Fir S.51°E., 18.6 ft. mkd. ¼ S21 CS BT.

BLM Dependent resurvey by Stephan L. Barott, Cadastral Surveyor (Forest Service, USDA) under Group #1995, surveyed April/Nov. 2002 - (DCSO records Vol. 54 Page(s) 21160-1)

The ¼ sec. cor. of secs. 20 & 21, perpetuated by the Douglas County Surveyor's Office, in 1967; monumented with an iron pipe, 2" dia., firmly set, projecting 17" above the ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree

A sawed pine stump, 35" dia., bears S.79¼°W., 51.1 ft., with illegible fragmentary scribe marks visible on decayed open face. (Record, S. 78°W., 51.5 ft.)

and bearing trees mkd. by the County Surveyor's Office

A fir, 18" dia., bears S.52½°E., 18.5 ft., with a healed double blaze.

A fir, 15 ins. diam., bears N.81½°W., 12.8 ft., with a healed double blaze.