

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8746-47)

Set a Fir post, 4 ft. long, 4" sq., 24" in the ground, marked T32S R7W S16 on NE.; S21 on SE.; S20 on SW.; and S17 on NW. faces, also 3 notches on S. and 4 notches on E. angle of same, from which:

- A Live Oak 8" dia., bears N.10°E., 31 lks. mkd. T32S R7W S16 BT.
- A Pine 12" dia., bears S.45°E., 56 lks. mkd. T32S R7W S21 BT.
- A Live Oak 6" dia., bears S.6°W., 19 lks. mkd. T32S R7W S20 BT.
- A Pine 9" dia., bears N.57°W., 33 lks. mkd. T32S R7W S17 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - Nov. 17, 1967 - C.S. File 54/36-140

Found - 8" now 11" Live Oak, N.10°E., 20.5 ft., opened and found scribing "BT".
12" now 28" Pine S.41°E., (Rec. S.45°E.) 37.8 ft., shows face.
6" now 10" Live Oak S.6°W., 12.5 ft. (Rec. 17.5 ft.), no scribing.
9" now 24" Pine N.57°W., 21.8 ft., opened and found no scribing.

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 7 W
S 17 | S 16
S 20 | S 21
1967

Rescribe-28" Pine S.41°E., 37.0 ft. mkd. T32S R7W S21 CS BT.
New BTs -20" D.Fir N.7°W., 36.0 ft. mkd. T32S R7W S17 CS BT.
18" D.Fir N.48°E., 26.0 ft. mkd. T32S R7W S16 CS BT.
14" D.Fir S.1°W., 26.7 ft. mkd. T32S R7W S20 CS BT.

Fd. and used in BLM resurvey by Roseberry and Aanrud, Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records, Vol. 42 Pages 16494-95)

BLM Dependent resurvey by Stephan L. Barott, Cadastral Surveyor (Forest Service, USDA) under Group #1995, surveyed April/Nov. 2002 - (DCSO records Vol. 54 Page(s) 21161-2)

continued next page

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The cor. of secs. 16, 17, 20, & 21, monumented with an iron pipe, 1¼" dia., firmly set, projecting 7" above the ground, with brass cap (properly) mkd., from which the original bearing trees

A live oak, 7" dia., bears N.16½°E., 20.5 ft., with no scribe marks visible on an open face.

A pine, 29" dia., bears S.41°E., 37.0 ft., with a healed blaze.

A live oak, 5" dia., bears S.6°W., 12.5 ft., with no scribe marks visible on a decayed open face.

A pine, 24" dia., bears N.57°W., 21.8 ft., with no scribe marks visible on a decayed open face.

and bearing trees mkd. by the County Surveyor's Office, reported by Roseberry & Aanrud

A fir, 27" dia., bears N.48°E., 25.7 ft., with a healed blaze.

A fir, 20" dia., bears S.1°W., 26.7 ft., with a healed blaze.

A fir, 35" dia., bears N.7°W., 36.0 ft., with a healed blaze.

The geographic position (NAD 1927) of the cor. of secs. 16, 17, 20, & 21, T32S R7W., as determined from a tie to Oregon Department of Transportation Control Station "AZAL" is as follows:

Latitude: 42°46'57.70" N. Longitude: 123°32'35.58" W.

From this point, Oregon Department of Transportation Control Station "AZAL" bears N.85°36'00"E., 78,497.01 ft. (mean bearing and sea level distance); monumented with an ORDOT Primary GPS brass disk, 4" dia., firmly set in a concrete collar, 8" dia., 1" below the surface of the ground, mkd. AZAL 1989 and a triangle.

Fd. DCSO & & BT per rec. 7/2014 - C.S. File 65/82-49