

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8748)

Set a Cedar post, 4 ft. long, 4" sq., 20" in the ground, marked ¼ S on the W. side for the ¼ sec. cor., from which:
A Pine 40" dia., bears S.30°E., 20 lks. mkd. ¼ S BT.
A Pine 40" dia., bears S.45°W., 63 lks. mkd. ¼ S BT.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records Vol. 42 Page(s) 16495)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked

T 32 S R 7 W
1/4
S 17 | S 16
1978

from which

A Fir 8" dia., bears N.88½°E., 53 lks. mkd. ¼ S16 BT.
A Fir 6" dia., bears S.38°W., 82 lks. mkd. ¼ S17 BT.

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 7/2014 - C.S. File 65/82-51

Found - BLM brass cap (properly mkd)

14" Fir N.88°E., 35.0 ft. good scar.

13" Fir S.38°W., 54.1 ft. good scar.

New - 34" Fir N.35°W., 40.3 ft. scribed ¼ S17 BT.

14" Fir S.33°E., 49.8 ft. scribed ¼ S16 BT.

Note - Compass decl. 15½°E.