

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Pg 8748)

Set a Pine post, 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 8. 9. 16 and 17 marked T32S R7W S9 on NE.; S16 on SE.; S17 on SW.; S8 on NW.; also 4 notches on S. and 4 notches on E. angles of same, from which:

A Fir 24" dia., bears N.55°E., 126 lks. mkd T32S R7W S9 BT
A Fir 40" dia., bears S.88°E., 89 lks. mkd T32S R7W S16 BT
A Pine 10" dia., bears S.28°W., 75 lks mkd T32S R7W S17 BT
A Pine 36" dia., bears N.24°W., 91 lks. mkd T32S R7W S8 BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - Nov. 1967 - C.S. File 54/36-135

Found - Orig. 24" D.Fir, now snag, N.55°E., 83.2 ft., no scribing.
Orig. 40" D.Fir, now down, S.88°E., 58.7 ft., no scribing.
Orig. 10" now 38" Pine, S.28°W., 49.5 ft., opened for scribe "T".
Orig. 36" Pine, now snag, N.24°W., 60.1 ft., tree opened previously, no scribing found.

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 7 W
S 8 | S 9
S 17 | S 16
1967

New BTs -8" D.Fir S.60°W., 7.9 ft. mkd. T32S R7W S17 CS BT.
13" Y.Pine N.45°W., 13.0 ft. mkd. T32S R7W S8 CS BT
13" D.Fir N.51°E., 32.5 ft. mkd. T32S R7W S9 CS BT.
14" Y.Pine S.78°E., 34.0 ft. mkd. T32S R7W S16 CS BT

Cor. Fd. and used in BLM resurvey by Roseberry and Aanrud, Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records, Vol. 42 Page 16496)

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 7/2014 - C.S. 65/82-50

Found - DCSO Brass cap (properly mkd)
22" Fir N.51°E., 23.5 (rec. 32.5) good scar
23" Pine S.78°E., 34.0 ft. good scar.
14" Fir S.60°W., 7.9 ft. good scar.

New - 14" madrone N.58°W., 22.4 ft. scribed T32S R7W S8 BT

Note - Compass decl. 15½°E.