

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8751)

Set a Cedar post 4 ft. long, 4" sq., 18" in the ground, ¼ S on W. side for the ¼ sec. cor., from which
A Fir 15" dia., bears N.40°E., 24 lks. mkd. ¼ S BT.
A Fir 18" dia., bears S.65°W., 22 lks. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - November 1967 - C.S. File 54/36-97

Found - Orig. 15" now 18" D.Fir N.40°E., 15.8 ft. shows faint bark scribe, / S BT
Orig. 18" D.Fir now 8 ft. stob, S.65°W., 14.5 ft. shows bark scribe, ¼ S B

Set Brass cap at ¼ cor. mkd: County Surveyors Office
T 32 S R 7 W
¼ S 5 | S 4
1967

New BT - 14" D.Fir S.48°W., 16.8 ft. scribed ¼ S5 CS BT.
Rescribe-18" D.Fir N.40°E., 15.8 ft. mkd. ¼ S4 CS BT.