

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8744)

Set a Fir post, 4 ft. long, 4" sq., 18" in the ground marked ¼ S on N. side for the ¼ sec. cor., from which
A Fir 16" dia., bears S.22°E., 32 lks. dist., mkd. ¼ S BT.
A Fir 16" dia., bears N.15°W., 48 lks. dist., mkd. ¼ S BT.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - March/Aug. 1954 - C.S. File 41/301

Determined at the record bearing and distance from each of the old bearing trees.
At the corner point
Set an Iron pipe 3 ft. long, 1½" dia., 28" in the ground, mkd. RS33; from which the original bearing trees:
A D.Fir 20" dia., bears S.22°E., 32 lks. dist., mkd. on bark ¼ S BT.
A D.Fir 28" dia., bears N.15°W., 48 lks. dist., mkd. on bark ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - March 1968 - C.S. File 54/36-119

Found - 1½" Iron pipe at ¼ corner.
20" D.Fir, now stob, S.22°E., 21.1 ft., no evidence of scribing.
28" D.Fir, now 30", N.15°W., 31.7 ft., faint bark scribe "¼S".
Reblazed and rescribed:
28" D.Fir now 29", N.15°W., 31.7 ft. mkd. "¼ S28 CS BT"
New BT - 24" D.Fir S.38°W., 21.0 ft. mkd. "¼ S33 CS BT".
This corner lies approx. 80 ft. W. of deep ravine, running NW

Survey by Mark Smalley, L.S. #2354 - For: Roseburg Resources - July 1993 - M 117-48

Found - 1½" Iron pipe.
34" Fir N.15°W., 31.7 ft., healed face.
16" Fir S.22°E., 21.1 ft. rotten stump.
30" Fir S.38°W., 21.0 ft. healed face.
Scribed -11" Madrone N.14°E., 25.5 ft. "¼ S28 BT".
18" Fir S.79°W., 74.5 ft. "¼ S33 BT".

Found OK by R. Templin, July 1995 - M122-53

