

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 340240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Section 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - Dec. 1954/May 1956 - C.S. File 42/142

-----  
Point for corner determined by intersection of N-S and E-W centerlines.

Set an Iron post at point of intersection, 3 ft. long, 1½" dia., 42" in the ground mkd. RS33, from which

A D.Fir 14" dia., bears N.27°E., 95 lks. mkd. C ¼ S28 RS33 BT.

An I.Cedar 14" dia., bears S.26°E., 209 lks. mkd. C ¼ S28 RS33 BT.

Survey by Mark Smalley, L.S. #2354 - For: Roseburg Resources Co. - July 1993 - M 117-48

-----  
Found - 1½" Iron Pipe  
14" Fir, N.27°E., 62.7 ft., snag, scribe visible.  
14" Cedar, S.26°E., 137.9 ft., down & rotten.

New BTs -12" Cedar S.30°E., 100.6 ft., "C ¼ S BT".  
14" Fir, S.26°W., 48.4 ft., "C ¼ S BT".  
8" Fir, N.46°E., 18.7 ft., " ¼ S BT".  
14" Fir, N.8°W., 52.0 ft., "C ¼ S BT".