

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Pg 8746)

Set a Laurel post, 4 ft. long, 4" sq., 20" in the ground, marked ¼ S for the ¼ sec. cor., from which

A Pine 20" dia., bears S.38°W., 22 lks. mkd. ¼ S BT.

A Pine 24" dia., bears N.45°W., 17 lks. mkd. ¼ S BT.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - Dec.1954/May 1956 - C.S. File 42/142

Determined at the record distance from each original bearing tree.

Set an Iron pipe 3 ft. long, 1½" dia., 28" in the ground, mkd. RS33. From which the original bearing trees:

A dead Yellow Pine 28" dia., bears N.44°W., 17 lks. dist., with blazes mutilated.

A dead Yellow Pine 24" dia., bears S.33°W., 22 lks. dist., with blazes mutilated.

And new bearing trees:

A TanOak 5" dia., bears N.60°E., 18½ lks. dist., mkd. ¼ S21 RS33 BT.

A TanOak 5" dia., bears S.5°W., 26 lks. dist., mkd. ¼ S28 RS33 BT.

Fd. OK, Approx. 1300' east of road at ? of Dad's Creek. By DCSO, J.Powell, Dec. 13, 1967, C.S. File 54/36-116

BLM remonumentation by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records Vol. 42 Page(s) 16511)

The ¼ sec. cor., perpetuated and recorded by Price in 1954, monumented with an iron pipe, 1½" dia., firmly set, projecting 8" above ground, from which the remains of the original bearing trees:

A Pine stump 28" dia., bears N.42°W., 17 lks. dist., with healed double blaze. (Rec. N.45°W.)

A Pine stump 24" dia., bears S.35°W., 22 lks. dist., with healed double blaze. (Rec. S.38°W.)

and the remains of bearing trees mkd. by Price:

A dead topped TanOak 6" dia., bears N.60°E., 18½ lks. dist., with scribe marks ¼ S21 RS33 BT visible on partially healed blaze.

A TanOak snag 5" dia., bears S.5°W., 26 lks. dist., with scribe marks ¼ S28 RS33 BT visible on partially healed blaze.

(Cont. Next Page)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, directly over iron pipe, with brass cap marked

T 32 S R 7 W

¼ S 21
S 28

1978

from which a new bearing tree:

A Fir 7" dia., bears S.13°E., 43 lks. dist., mkd. ¼ S28 BT.

Survey by Mark Smalley, L.S. #2354 - For: Roseburg Resources Co. - July 1993 - M 117-48

Found - 1978 Cadastral BCIP
12" Fir, S.13°E., 28.4 ft, bark scribed faced and rescribed "¼ S28 BT"
28" Pine, N.45°W., 11.2 ft. - Dead.
5" Tan Oak, N.60°E., 12.2 ft. - Dead, scribe visible.
5" Tan Oak, S.5°W., 17.2 ft. - Dead, scribe visible.
Scribed -7" Fir, S.53°W., 20.2 ft., "¼ S28 BT"
6" Fir, N.10°W., 12.0 ft., "¼ S21 BT"
7" Fir, S.46°E., 21.5 ft., "¼ S28 BT"