

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8749)

Set a Cedar post, 4 ft. long, 18" in the ground, mkd. ¼ S on N. side for the ¼ sec. cor., from which
A Cedar 24" dia., bears S.50°W., 31 lks. mkd. ¼ S BT.
A Pine 30" dia., bears N.70°W., 78 lks. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - Nov. 13, 1967 - C.S. File 54/36-146

Found - 24" now 30" Cedar S.50°W., 20.5 ft., shows scribing, "4S".

30" now 38" Pine N.70°W., 51.5 ft., shows face.

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 7 W

¼ S 9
S 16

1967

New BTs -10" Fir S.73°W., 10.4 ft. mkd. ¼ S16 CS BT.

10" Fir N.35°W., 9.5 ft. mkd. ¼ S9 CS BT.

Note - This corner is on steep south slope.

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 7/2014 - C.S. File 65/82-52

Found - DCSO Brass cap (properly mkd)
42"x2' tall cedar stump vis. scribed S.50°W. 20.5 ft

20" Fir S.73°W., 10.4 good scar.

40" decayed pine stump N.70°W., 51.5 ft.

16" Fir N.35°W., 9.5 ft. good scar.

New - 16" cedar S.52°E., 38.9 ft. scribed ¼ S16 BT.

22" fir N.27°E., 21.4 ft. scribed ¼ S9 BT.

Note - Compass decl. 15½°E.