

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8750)

Set a Laurel post, 4 ft. long, 4" sq., marked $\frac{1}{4}$ S on N. side for $\frac{1}{4}$ sec. cor., from which
A Cedar 5" dia., bears S.48°E., 50 lks. mkd. $\frac{1}{4}$ S BT.
A Fir 30" dia., bears N.35°W., 11 lks. mkd. $\frac{1}{4}$ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - November 1967 - C.S. File 54/36-96

Found - Orig. 5" Cedar, now down, S.48°E., 33.0 ft., no trace of scribing.
Orig. 30" now 35" Fir, N.35°W., 7.3 ft., bark scribe visible " $\frac{1}{4}$ S"

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 7 W
 $\frac{1}{4}$ $\frac{S \ 4}{S \ 9}$
1967

New BT - 8" D.Fir S.57°E., 17.3 ft. mkd. $\frac{1}{4}$ S9 CS BT.
Rescribe-35" D.Fir N.35°W., 7.3 ft. mkd. $\frac{1}{4}$ S4 CS BT. (This distance is orig. dist. from face.)

Fd. BC & accessories by G Neitsch, 11/2022 - M181-49