

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 4; and 33 of T31-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16, 1881 (DCSO records Vol. 19 Page(s) 8026)

Set a Laurel post 4 ft. long, 4" sq., 18" in the ground, marked 1/4 S on N. side for the 1/4 sec. cor., from which
A Fir 15" dia., bears S.70°E., 45 lks. mkd. 1/4 S BT.
A Fir 15" dia., bears N.70°W., 52 lks. mkd. 1/4 S BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531, surveyed Oct. 1963\June 1964 (DCSO records Vol. 33 Page(s) 13621)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked
T 31 S R 7 W
1/4 $\frac{S \ 33}{S \ 4}$
T 32 S R 7 W
1964
from which
A Fir 8" dia., bears N.42 3/4°E., 37 lks. mkd. 1/4 S33 BT.
A Fir 6" dia., bears S.22 3/4°E., 14 1/2 lks. mkd. 1/4 S4 BT.

Douglas Co. Surveyors Office - John M. Powell; Frank Jones and Cliff Stone, crew - Dec. 21, 1966 - C.S. File 54/36-67

Found - GL0 brass cap, S.82°E., 19.1 ft.
Orig. 15" now 38" D.Fir S.70°E., 29.7 ft., bark scribed, faint "BT".
Orig. 15" now 32" D.Fir N.70°W., 34.3 ft., bark scribed.
Set Brass cap at 1/4 cor. mkd: County Surveyors Office
T 31 S
1/4 $\frac{S \ 33}{S \ 4}$ R7W
T 32 S
1966
Reblazed and rescribed:
38" D.Fir S.70°E., 29.7 ft. mkd. 1/4 S4 CS BT.
7" D.Fir N.42°E., 18.8 ft. mkd. 1/4 S33 CS BT.
This corner lies in small draw about 400.0 ft. West of creek.

(Cont. Next Page)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 4; and Sec. 33, T31-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531, surveyed June 1967 (DCSO records Vol. 34 Pg 13970)

The ¼ sec. cor., perpetuated and recorded by Powell in 1966, monumented with an iron post, 1" dia., firmly set, protruding 12" above ground, with brass cap properly marked.

from which the original bearing trees:

A Fir 37" dia., bears N.70°W., 53½ lks. dist., with scribe marks ¼ S BT visible on bark blaze. (Rec. dist., 52 lks.)

A Fir 41" dia., bears S.70°E., 46½ lks. dist., with scribe marks BT visible on bark blaze, and remarked ¼ S4 CS BT by Powell. (Rec. dist. 45 lks.)

and a bearing tree mkd. in 1963-64

A Fir 9" dia., bears N.65°E., 54 lks. dist., mkd. ¼ S33 BT and a bearing tree mkd. by Powell

A Fir 7" dia., bears N.40°E., 29 lks. mkd. ¼ S33 BT.

From this point, the ¼ sec. cor. of secs. 4 and 33, established in 1963-64, bears S.83°E., 0.29 chs. dist. Remove the iron post and destroy the marks on the SE. BT.

Survey by Kristian DeGroot, L.S. #1941 - For: Allen & Gibbons Logging - Nov. 28, 1983 - C.S. File 58/229-22

Found - 1966 DCSO brass cap, properly mkd. on a 1" I.P., bent, loosely set and disturbed during logging activity.

I reset the monument from the original bearing trees:

36" D.Fir stump bears S.67½°E., 30.4 ft. with scribe marks "S4" visible on an opened blaze. (Rec. S.70°E., 29.7 ft.)

30" D.Fir stump bears N.67½°W., 35.0 ft. with bark scribe marks "¼S" visible on a sawed out block. (Rec. N.70°W., 34.3 ft.)

A 1966 BT, a 9" D.Fir 8 ft. high stump, partially uprooted, bears N.42°E., 18.8 ft. with healed blaze.

A 1967 BLM BT, a 12" D.Fir, uprooted stump, its root hole bears N.65°E., 35.6 ft.

New BT - 5" D.Fir bears N.32½°E., 67.6 ft. scribed ¼ S33 BT with a brass washer "LS 1941" nailed into lower blaze.

Distance to new BT to a nail in root crown at the side and center of the tree. I painted 6" red bands around new BTs and all BT faces red and attached BT tags.

Fd. BC & accessories by G Neitsch, 11/2022 - M181-49 _____