

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8738)

-----  
Set a Fir post 4 ft. long, 4" sq., 24" in ground, marked ¼ S on W. side for ¼ sec. cor., from which  
A S.Pine 24" dia., bears S.40°E., 8 lks. mkd. ¼ S BT.  
A Cedar 20" dia., bears N.42°W., 30 lks. mkd. ¼ S BT.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - March/Aug. 1954 - C.S. File 41/301

-----  
Determined at the record distance from each old bearing tree. At the corner point  
Set an Iron pipe, 3 ft. long, 1½" dia., 28" in the ground, mkd. RS33,  
from which the original bearing trees:  
A Sugar Pine 42" dia., bears S.40°E., 8 lks. dist., with blazes healed.  
An Incense Cedar 24" dia., bears N.42°W., 30 lks. dist., mkd. on bark ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - Dec. 1967 - C.S. File 54/36-131

-----  
Found - 1½" Iron pipe at ¼ corner.  
Orig. 42" S.Pine now 24 ft. stob, S.40°E., 5.3 ft., shows old scars.  
Orig. 24" now 25" Cedar N.42°W., 19.8 ft. shows faint scribe marks, not legible.  
New BTs -14" D.Fir N.56°W., 23.9 ft. mkd. ¼ S33 CS BT.  
6" D.Fir N.38°E., 16.3 ft. mkd. ¼ S34 CS BT.

Found OK by R. Templin, July 1995 - M122-53