

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8735-36)

-----  
Set a Chinquapin post, 4 ft. long, 4" sq., 20" in the ground for the cor. to secs. 21, 22, 27 and 28 marked T32S R7W Sec. 22 on NE.; Sec. 27 on SE.; S28 on SW.; and S21 on NW.; also 2 notches on the S. and 3 notches on E. angles, from which  
A Fir 30" dia., bears N.35°E., 34 lks. mkd. T32S R7W S22 BT.  
A Chinquapin 10" dia., bears S.30°E., 90 lks. T32S R7W S27 BT.  
A Fir 24" dia., bears S.62°W., 30 lks. T32S R7W S28 BT.  
A Laurel 8" dia., bears N.50°W., 43 lks. T32S R7W S21 BT.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - Sept. 1954/April 1955 - C.S. File 41/373

-----  
Determined at record bearing and distance from original NE., SW., and NW., bearing trees.  
At the corner point  
Set an Iron pipe, 3 ft. long, 2" dia., 28" in the ground, mkd. RS33; from which the original bearing trees:  
A D.Fir 32" dia., bears N.25°E., 34 lks. dist., mkd. on bark T32S R7W S22 BT.  
A D.Fir 30" dia., bears S.62°W., 30 lks. dist., mkd. on bark T32S R7W S28 BT.  
A Madrona 12" dia., bears N.50°W., 43 lks. dist., with blaze healed.  
There is no remaining evidence of the original SE BT.

Bruce Shaner - For: Roseburg Resources - March 2002 - M137-35 & C.S. File 65/42-18

-----  
Found - 2" iron pipe, from which a:  
36" D.Fir BT, bark scribes visible, bears N.30°E., (Rec. N.25°E.), 22.4 ft.  
34" D.Fir BT, bark scribes visible, bears S.62°W., 19.8 ft.  
20" Madrone BT, face overgrown, bears N.50°W., 26.2 ft. (rec. 28.4 = slope distance)  
New - 10" Madrone BT, I scribed "T32S R7W S27 BT" on bark, bears S.15°E., 16.0 ft.  
6 ft. steel fence post bears South 1.0 ft.