

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8737)

Set a Fir post 4 ft. long, 4" sq., 18" in the ground and marked ¼ S on W. side for ¼ sec. cor., from which
A Fir 24" dia., bears N.55°E., 31 lks. dist. mkd. ¼ S BT.
A Laurel 16" dia., bears S.60°W., 28 lks. mkd. ¼ S BT.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - Sept. 1954/April 1955 - C.S. File 41/373

Determined at record bearing and distance from the only extant original bearing tree.
At the corner point
Set an Iron pipe, 3 ft. long, 1½" dia., 28" in the ground, mkd. RS33, from which the extant original BT:
A D.Fir 30" dia., bears N.55°E., 31 lks. dist., mkd. on bark ¼ SBT.
And a new bearing tree:
A D.Fir 9" dia., bears N.77½°W., 84 lks. dist. mkd. ¼ S21 RS33 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - November 3-6, 1967 - C.S. File 54/36-90

Found - 1½" Iron pipe.
Orig. 30" now 40" D.Fir N.55°E., 20.5 ft. very faint bark scribe, 1/
9" now 13" D.Fir N.77½°W., 55.4 ft. shows good scar.
New BT - 10" D.Fir S.89°E., 42.5 ft. mkd. ¼ S22 CS BT.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records Vol. 42 Page(s) 16510)

The ¼ sec. cor., perpetuated and recorded by Price in 1954, and further perpetuated and recorded by Powell in 1967, monumented with an iron pipe 1½" dia., firmly set, projecting 8" above ground, from which the remains of an original bearing tree:
A sawed Fir stump 40" dia., bears N.55°E., 33 lks. dist., with scribe marks ¼ S visible on bark blaze. (Rec. 31 lks.)
and a bearing tree mkd. by Price
A Fir 16" dia., bears N.77½°W., 84 lks. dist., with healed blaze.
(Cont. Next Page)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a bearing tree mkd. by Powell
A Fir 14" dia., bears S.89°E., 64½ lks. dist., with healed
blaze.

At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in
the ground, directly over iron pipe, with brass cap marked

T 32 S R 7 W
1/4
S 21 | S 22
1978