

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO recs Vol 21 Page 8737)

Set a Pine post, 4 ft. long, 4" sq., 22" in the ground for the cor. to secs. 15, 16, 21 and 22 marked T32S R7W S15 on NE.; S22 on SE.; S21 on SW.; S16 on NW.; also three notches on S. and E. corners, from which

A Pine 8" dia., bears N.28°E., 21 lks. mkd. T32S R7W S15 BT
A Pine 10" dia., bears S.20°E., 32 lks. mkd. T32S R7W S22BT
A Pine 36" dia. bears S.75°W. 135 lks mkd. T32S R7W S21 BT
A Pine 16" dia. bears N.25°W. 36 lks. mkd. T32S R7W S16 BT

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - Sept. 1954/April 1955 - C.S. File 41/373

Determined at the record bearing and distance from each original bearing tree.

At the corner point

Set an Iron pipe 3 ft. long, 2" dia., 28" in the ground, mkd. RS33; from which the original bearing trees:

A Yellow Pine 10" dia., bears N.28°E., 21 lks. dist., with the scribe marks W S15 uncovered.
A Y.Pine 16" dia., bears S.20°E., 32 lks. dist. with partial scribe marks visible.
A Y.Pine 40" dia., bears S.75°W., 135 lks. dist., with blaze healed.
A Sugar Pine 28" dia., bears N.25°W., 36 lks. dist. with blaze healed.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - Nov. 1967 - C.S. File 54/36-145

Found - 2" I.Pipe at corner.

Orig. 10" Y.Pine now stob, N.28°E., 13.4 ft. scribe visible "W S15"

Orig. 16" Y.Pine now down, S.20°E., 21.1 ft.

Orig. 40" Y.Pine now snag, S.75°W., 89.1 ft., shows old axe work.

Orig. 28" now 39" S.Pine N.25°W., 23.8 ft shows scar

New BTs - 5" Cedar S.71½°W., 47.7 ft. mkd. S21 CS BT.

7" D.Fir N.86°W., 32.0 ft. mkd. T32S R7W S16 CSBT

7" Laurel N.54°E., 41.5 ft. mkd. T32S R7W S15 CSBT

30" D.Fir S.81½°E., 11.9 ft. mkd. T32S R7W S22 CSBT

DCSO-GIS Corner visitation - 2/17/2004 - Typed: 2/10/2011 - C.S. File 67/33-1

Monument - 2" IP Comment - ok

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 7/2015 - C.S.
File 65/89-11

Found - 2" iron pipe
9" Madrone N.54°E., 41.5 ft. vis. scribe.
41" D.Fir S.81°E., 11.9 ft. good scar.
13" Cedar, S.71°W., 47.7 ft. good scar.
18" Fir N.86°W., 32.0 ft. (No record tagged by J
Powell 11/15/1967)
34" S.Pine snag N.25°W., 23.8 ft. good scar.
Note - Hand held Lat & Long N.42°46.935 W. 123°31.510
Corner is at the NW corner of clear cut unit approx.
150 west of road.
Compass decl. 15½°E.