

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8738)

Set a Laurel post 4 ft. long, 4" sq., 20" in ground, mkd. ¼ S on W. side for ¼ sec. cor., from which
A Pine 60" dia., bears S.50°E., 31 lks. mkd. ¼ S BT.
A Laurel 10" dia., bears N.48°W., 70 lks. mkd. ¼ S BT.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records Vol. 42 Page(s) 16510-11)

The ¼ sec.cor., determined at record bearing from the remains of the original bearing trees:

A Sugar Pine, snag, 60" dia., bears S.50°E., 34 lks. dist., with illegible scribe marks visible on detached portion of bark. (Rec. 31 lks.)
A Madrone with burned out center, 20" dia., bears N.48°W., 70 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked
T 32 S R 7 W
1/4
S 16 | S 15
1978

from which new bearing trees:

A Fir 9" dia., bears N.71½°E., 63 lks., mkd. ¼ S15 BT.
A Fir 25" dia., bears N.64½°W., 61 lks., mkd. ¼ S16 BT.

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 7/2015 - C.S. File 65/89-13

Found - BLM brass cap
15" Fir, N.71°E., 41.6 ft. good scar.
54" Sugar Pine snag, S.50°E., 22.4 ft.
31" Fir, N.64°W., 40.3 ft. good scar.
20" Madrone N.48°W., 46.2 good scar.
New - 6" madrone S.63°W., 24.7 ft. scribed ¼ S16 BT.
Note - Hand held Lat & Long: N.42°47.377 W.123°31.503
Compass decl. 15½°E.