

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8738-39)

Set a Fir post, 4 ft. long, 4" sq., 20" in the ground for the cor. to secs. 9, 10, 15 and 15 marked T32S R7W S10 on NE.; S15 on SE.; S16 on SW.; S9 on NW.; faces, also 4 notches on S. and 3 on E. angles of same, from which:

- A Fir 5" dia., bears N.17°E., 62 lks. mkd. T32S R7W S10 BT.
- A Fir 48" dia., bears S.48°E., 90 lks. mkd. T32S R7W S15 BT.
- A Laurel 7" dia., bears S.35°W., 31 lks. mkd. T32S R7W S16 BT.
- A Laurel 6" dia., bears N.51°W., 92 lks. mkd. T32S R7W S9 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - Nov. 22, 1967 - C.S. File 54/36-134

Found - Orig. 5" now 27" D.Fir N.17°E., 40.9 ft. tree opened before, scribe visible.

Orig. 48" D.Fir now rotten stump, S.48°E., 56.4 ft. (rec. 59.4')

No trace of SW or NW (6" & 7") Laurel BTs,

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 7 W
S 9 | S 10
S 16 | S 15
1967

New BTs -26" D.Fir S.45°E., 28.4 ft. mkd. T32S R7W S15 CSBT
10" D.Fir S.23½°W., 12.6 ft. mkd. T32S R7W S16 CSBT
27" D.Fir N.5°W., 15.7 ft. mkd. T32S R7W S9 CS BT.