

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8742)

-----  
Set a Laurel post, 4 ft. long, 4" sq., 20" in the ground, mkd.  $\frac{1}{4}$  S on W. side for the  $\frac{1}{4}$  sec. cor., from which  
A Laurel 6" dia., bears S.25°E., 10 lks. dist., mkd.  $\frac{1}{4}$  S BT.  
A Fir 6" dia., bears West, 8 lks. dist.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #543, surveyed June, 1964 (DCSO records Vol. 33 Page(s) 13654)

-----  
Point for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked  
T 32 S R 7 W  
 $\frac{1}{4}$   
S 4 S 3  
1964

from which  
A Fir 24" dia., bears N.66 $\frac{1}{2}$ °E., 4 lks. dist., mkd.  $\frac{1}{4}$  S3 BT  
A Fir 15" dia., bears S.71°W., 41 lks. dist., mkd.  $\frac{1}{4}$  S4 BT