

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION S. 1/4 Cor. Sec. 34 only,

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8703)

Marked face of steep rocky ledge and made stone mound 4 ft. sq. 3 ft. high for the ¼ sec. cor., from which
A Live Oak 14" dia., bears North, 14 lks. dist., mkd. S C ¼ S BT.
A Fir 15" dia., bears S.76°E., 23 lks. dist., mkd. S C ¼ S BT.

Not found, cor. probably taken by rail rd or telephone lines. by J.P 12/1967 - C.S. file 54/36-125 (added 10/12/2016)

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #845, surveyed April/Nov. 1975 (DCSO records Vol. 41 Page(s) 16269)

Point for the standard ¼ sec. cor. of sec. 34, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked
S C
T 32 S R 7 W
¼ S 34
1975

from which
A Fir 9" dia., bears N.38°E., 102 lks. dist., mkd. ¼ S34 SC BT.
A Fir 6" dia., bears N.60°W., 187½ lks. dist., mkd. ¼ S34 SC BT.