

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8735)

-----  
Set a Chinquapin post, 4 ft. long, 4" sq., 24" in the ground, marked ¼ S on the N. side for the ¼ sec. cor., from which  
A Laurel 16" dia., bears S.8°E., 37 lks. dist. mkd. ¼ S BT  
A Laurel 20" dia., bears N.72°W., 66 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John Powell & Crew - 3/20/1968  
(added 10/18/2016) - C.S. File 54/36-159

-----  
Not Found  
Good call at 45.50. Area has old large laurels that have been burnt out parts of trees which is not burnt all have been opened good E-W blazed. line.

Survey by Ronald Quimby, LS #1654 - For: Boise Cascade Timberlands of Oregon - May 1983 - M 94-27

-----  
Set 2½" x 30" alum. pipe, 26" in ground with 3" cap mkd. "T32S R7W WM 1/4 S27 S34 1983 RLS 1654".  
New BTs -6" Tan Oak bears N.50°W., 5.4 ft. faced and scribed "¼ S27 BT"  
14" D.Fir bears S.3°E., 44.0 ft. faced and scribed "¼ S34 BT"

Fd. Ok by Bruce Shaner - For: Roseburg Resources - March 2002 - M137-35 & C.S. File 65/42-11 - Added 6' iron post West 1 ft