

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8736)

Set a Cedar post 4 ft. long, 4" sq., 24" in the ground with stone mound about the same, marked $\frac{1}{4}$ S on N. side for the $\frac{1}{4}$ sec. cor., from which

A Laurel 20" dia., bears N.5°E., 82 lks. dist., mkd. $\frac{1}{4}$ S BT.

A Fir 20" dia., bears S.80°E., 45 lks. dist., mkd. $\frac{1}{4}$ S BT.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - Sept. 1954/April 1955 - C.S. File 41/373

Determined at the record dist. from each original BT.

At the corner point,

Set an Iron pipe, 3 ft. long, 1½" dia., 2" in the ground to bedrock, and in a mound of stone to top, mkd. RS33; from which the original bearing trees:

A Madrona 20" dia., bears N.18°E., 82 lks. dist., with old blaze burnt.

A D.Fir 34" dia., bears S.75°E., 45 lks. dist., with the scribe marks $\frac{1}{4}$ on charred bark blaze.

And new bearing trees:

An Incense Cedar 8" dia., bears N.86°E., 66 lks. dist., mkd. $\frac{1}{4}$ S22 RS33 BT.

An I.Cedar 36" dia., bears South, 54 lks. dist., mkd. $\frac{1}{4}$ S27 RS33 BT.

Fd. ok by Bruce Shaner - March 2002 - M137-35 & C.S. File 65/42-19. Note: Corner sets in rocky opening