

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8739)

Set a Cedar Post 4 ft. long, 4" sq., 24" in the ground for the $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on N. Side, from which
A Fir 40" dia., bears N.35°E., 14 lks. mkd. $\frac{1}{4}$ S BT.
A Fir 40" dia., bears S.1°W., 22 lks. mkd. $\frac{1}{4}$ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - Nov. 1967 - C.S. File 54/36-144

Found - Orig. 40" D.Fir now stump, N.35°E., 9.2 ft. bark scribe visible, $\frac{1}{4}$ S
Orig. 40" D.Fir now stump, S.1°W., 14.5 ft. stump pushed out of ground.

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 7 W

$\frac{1}{4}$ $\frac{S}{S}$ $\frac{10}{15}$

1967

New BTs -15" Laurel N.51°W., 15.4 ft. mkd. $\frac{1}{4}$ S10 CS BT.

8" D.Fir S.44°E., 3.5 ft. mkd. $\frac{1}{4}$ S15 CS BT.

This corner lies approx. 260 ft. East of creek and old logging road.