

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8724-25)

Set a Laurel post, 4 ft. long, 4" sq., for the corner to secs. 26, 27, 34 and 35, marked T32S R7W S26 on NE.; S35 on SE.; S34 on SW.; and S27 on NW. faces, also one notch on S. and two on E. angles of same, from which

A Laurel 5" dia., bears N.32°E., 61 lks. dist. marked T32S R7W S26 BT.

A Pine 26" dia., bears S.75°E., 340 lks. dist. marked T32S R7W S35 BT.

A Laurel 5" dia., bears S.60°W., 23 lks. dist. marked T32S R7W S34 BT.

A Laurel 5" dia., bears N.40°W., 43 lks. dist. marked T32S R7W S27 BT.

Douglas Co. Surveyors Office - John Powell - 3/20/1968 (added 8/9/2016) - C.S. File 54/36-159

Reported as not found

32" Pine S.75°E., 224.4 Orig.? cruisers marks & tagged no scribing fd. No trace of 3-5" Laurels. Location tag at approx. sec. cor.

Douglas Co. Surveyors Office - R.B. Kimberling - P.L. Earle - 2/28/1978 (added 8/9/2016) - C.S. File 59/46-22

Reported as not found.

Found - A squared wooden post set in 1968 by J. Powell as an approximate corner set by staff compass and tape.

A 24" Pine snag bears approx. S.75°E., 224.4 ft. with very deep chopping but no remaining evidence of a blaze or scribing.

Sec. line is brushed East & West - crosses Rd. #32-7-34 above switch back.

Survey by Ronald Quimby, L.S. #1654 - For: Boise Cascade Timberlands of Oregon - May 1983 - M 94-27

Found - 26" Pine stump bears S.79°E., 224.4 ft., with axe work.

Dead Madrone root cluster, bears S.60°W., 15.2 ft.

Madrone root cluster bears N.32°E., 40.3 ft.

Set 2½" x 30" alum. pipe 24" in ground with 3" cap mkd: T32S R7W S27 S26 S34 S35 1983 RLS 1654.

New BTs -9" Madrone bears S.70°E., 39.8 ft., faced and scribed T32S R7W S35 BT. (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias	Description
Alias	Description
Alias	Description
Alias	Description

29" D.Fir bears S.83°W., 84.6 ft., faced and scribed
T32S R7W S34 BT.
7" Madrone bears N.64°W., 38.3 ft. faced and scribed
T32S R7W S27 BT.
6" Live Oak bears N.34°E., 5.9 ft. faced and scribed
T32S R7W S26 BT.

BLM resurvey by Terrence Nickerson and Gordon Caster, under
Group #1528, surveyed March/April 1990 - (DCSO records Vol.
50 Page(s) 18990-91)

The Sec. cor., perpetuated and recorded by Quimby in 1983,
monumented with an alum. post, 2½" dia., firmly set,
projecting 4" above the ground with 1983 alum. cap, from
which the remains of the original bearing trees:
A Madrone root cluster, bears N.32°E., 61 lks.
A Ponderosa Pine stump 26" dia., bears S.79°E., 340 lks.
dist., no marks remain. (Rec. S.75°E.)
and bearing trees mkd. by Quimby:
A Live Oak 6" dia., bears N.34°E., 9 lks. dist., with
scribe marks T32S R7W S26 BT visible on partially
healed blaze.
A Madrone 10" dia., bears S.70°E., 60½ lks. dist., with
scribe marks T32S R7W S35 BT visible on partially
healed blaze.
A Fir 31" dia., bears S.83°W., 128½ lks. dist., with
pitched over blaze.
A Madrone 9" dia., bears N.64°W., 58 lks. dist. with
scribe marks T32S R7W S27 BT visible on partially
healed blaze.

From this point, the Bureau of Land Management Geodetic
Control Station No. EC 71084, at latitude 42°45'15.855 N.,
longitude 123°30'18.897" W. (NAD 1927), determined by the
Navstar Global Positioning System, bears N.12°44'23"W., 1.704
chs. dist., monumented with a finned alum. post, 3/4" dia.,
with alum. cap set flush with the ground, in concrete, mkd.
DEPT OF INTERIOR CONTROL SURVEY STATION EC 71084 1988 and a
triangle.

BLM Dependent resurvey by Stephan L. Barott, Cadastral
Surveyor (Forest Service, USDA) under Group #1995, surveyed
April/Nov. 2002 - (DCSO records Vol. 54 Page(s) 21157-8)

The cor. of secs. 26, 27, 34, & 35, monumented with an alum
post, 2½" dia., firmly set, flush with the ground, with
aluminum cap, oriented to the west, (properly) mkd.
from which the remains of BTs mkd. by Quimby, in 1983, and
reported by Nickerson & Caster continued next page

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A live oak snag, 8 ft. tall, 6" dia. bears N.36½°E., 5.9 ft., with scribe marks T32S R7W S26 BT visible on partially opened face. (Record, N.34°E.)

A sawed madrone stump, 6 ft tall, 10" dia. bears S.69½°E., 39.9 ft., with scribe marks T32S R7W S35 BT visible on partially opened face. (Record, S.70°E.)

A fir stump, 31" dia., bears S.81¼°W., 85.4ft., with a partially healed blaze. (Record, S.83°W., 84.8 ft.)

A madrone, 10 ins. diam., bears N.62°W., 37.9 ft., with a healed blaze. (Record, N.64°W., 38.3 ft.)

and a new bearing tree

A fir, 11" dia., bears S.37½°E., 115.0 ft. mkd. T32S R7W S35 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

The geographic position (NAD 1927) of the cor. of secs. 26, 27, 34, & 35, T32S R7W as determined from a direct tie to BLM Geodetic Control Station No. EC 71084 established in 1988, and shown on the official plat of survey accepted April 28, 1993, is as follows:

Latitude: 42°45'14.78" N. Longitude: 123°30'18.56" W.

From this point, the BLM Geodetic Control Station No. EC 71084 bears N.12°44'30"W., 112.31 ft.; (mean bearing and sea level distance), monumented with an aluminum post, set flush with the ground in concrete, with an aluminum cap mkd. DEPT OF INTERIOR CONTROL SURVEY STATION EC 71084 1988 and a triangle.

Ron Quimby - Crew: J. Leonard and N. Fromdahl - 1/2014 - C.S. File 65/82-18

Condition report

Found - Alum. cap (properly mkd)
32" Fir S.83°W., 84.6 ft. good scar.
12" madrona N.64°W., 38.3 (now burnt stump)

Note - Area badly burnt 7/2013
Compass decl. 15½°E.