

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Pg 8726)

Set a Pine post, for the ¼ sec. cor., 4 ft. long, 4" sq., 20" in the ground, marked ¼ S, from which
A Pine 14" dia., bears N.30°E., 88 lks. dist. mkd. ¼ S BT.
A Pine 30" dia., bears S.65°W., 148 lks. dist. mkd. ¼ S BT

Not fd DCSO J Powell, 3/20/1968 (added 10/2016) - C.S 54/36-159

Survey by Ronald Quimby, L.S. #1654 - For: Boise Cascade Timberlands of Oregon - May 1983 - M 94-27

Found - 56" P.Pine, burned out face, no marks visible, bears S.63°09'W., 97/7 ft. (Orig. BT)
28" P.Pine, sawn into, no marks visible, bears N.27°09'E., 58.1 ft. (Orig. BT)
Set 2½" x 30" alum. pipe 26" in ground, with 3" cap mkd: T32S R7W WM ¼ S27 S26 1983 RLS 1654.
New BTs -6" Sugar Pine bears S.84°W., 28.4 ft., faced and scribed ¼ S27 BT.
8" Tan Oak bears S.63°E., 6.1 ft., faced and scribed ¼ S26 BT.

Bruce Shaner - For: Roseburg Resources - March 2002 - M137-35 & C.S. File 65/42-20

Found - 2½" Alum. pipe with 2½" alum. cap, from which a:
56" Ponderosa Pine BT, orig. BT, burned out face - bears S.63°W., 97.7 ft.
28" Ponderosa Pine, OBT, now short snag, bears N.27°E., 58.1 ft. I rescribe "¼ S26 BT"
6" Sugar Pine BT, now snag, scribed visible, bears S.84°W., 28.4 ft.
10" Tan Oak BT, scribes visible bears S.63°E. 6.1 ft
New - 12" Madrone, bark scribed "¼ S27 BT" bears N.36°W., 16.2 ft.

Ron Quimby - Crew: J. Leonard and N. Fromdahl - 1/20/2014 - C.S. File 65/82-19

Condition report
Found - 3" alum cap. (properly mkd)
10" Tan Oak S.63°E., 6.1 ft., good scar.
13" Madrona N.36°W., 16.2 ft.
28" Pine snag N.27°E., 58.1 ft.
56" pine S.63°W., 97.7 ft., burnt face.
Note - Area burnt 7/2013 Compass decl. 15½°E.