

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8726)

Set a Laurel post 4 ft. long, 4" sq., 18" in the ground for the ¼ sec. cor. to secs. 22, 23, 26 and 27 marked T32S R7W S23 on NE.; S26 on SE.; S27 on SW.; and S22 on NW. faces, also two notches on S. and E. angles of same, from which
A Fir 36" dia., bears N.33°E., 18 lks. dist. marked T32S R7W S23 BT.
A Fir 14" dia., bears S.40°E., 22 lks. dist., marked T32S R7W S26 BT.
A Sugar Pine 36" dia., bears S.35°W., 30 lks. dist., marked T32S R7W S27 BT.
A Fir 30" dia., bears N.40°W., 14 lks. dist., marked T32S R7W S22 BT.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - Sept 1954/ April 1955 - C.S. File 41/373

Locus of corner detrmind by the record bearing from original NE. BT, and record bearings and distances from the original SE., SW., and NW BTs.
At the corner point
Set an iron pipe, 3 ft. long, 2" dia., 28" in the ground, mkd. RS33, from which the original bearing trees:
A D.Fir 54" dia., bears N.33°E., 68 lks. dist., mkd. on bark T32S R7W S23 BT.
A D.Fir 26" dia., bears S.40°E., 22 lks. dist., mkd. on bark T32S R7W S26 BT.
A D.Fir stump 30" dia., bears N.40°W., 14 lks. dist., on which no marks remain.
A Sugar Pine 48" dia., bears S.35°W., 30 lks. dist., with blazes healed.
The geographic position of this is lat. 42°46'05"N., and long. 123°30'14"W.

Douglas Co. Surveyors Office - John M. Powell, and crew - March 4, 1968 - C.S. File 54/36-128

Found - 1½" I.Pipe at corner.
Orig. 36" now 54" D.Fir N.33°E., 44.9 ft. (Rec. 11.9 ft.) faint bark scribe, T3
Orig. 14" now 26" D.Fir S.40°E., 14.5 ft., faint bark scribe, R W
Orig. 36" now 48" S.Pine S.35°W., 19.8 ft., nothing visible.

(Cont. Next Page)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. 30" D.Fir now stump N.40°W., 9.4 ft.
New BTs -13" D.Fir N.82°W., 74.0 ft. mkd. T32S R7W S22 CS BT.
Reblazed and rescribed:
54" D.Fir N.33°E., 44.9 ft. mkd. T32S R7W S23 CS BT.
26" D.Fir S.40°E., 14.5 ft. mkd. T32S R7W S26 CS BT.
48" S.Pine S.35°W., 19.8 ft. mkd. T32S R7W S27 CSBT

Fd. OK, by R. Quimby - May 1983 - M 94-27
Fd. OK, by M. Smalley, July 1993, M 117-43

Ron Quimby - Crew: J. Leonard and N. Fromdahl - 1/2014 - C.S.
File 65/82-17

Found - 1½" I.Pipe
54" fir snag N.33°E., 44.9 ft. badly burnt.
60" Pine S.35°W., 19.8 ft. burned scar.
26" fir stump S.40°E., 14.5 ft. badly burnt.
28" fir N.82°W., 74.0 ft. good scar.
Note - Area badly burnt 7/2013