

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8727)

-----  
Set Laurel post 4 ft. long, 4" sq., 18" in the ground for the 1/4 sec. cor. marked 1/4 S on W. side, from which  
A Fir 22" dia., bears East 50 lks. mkd. 1/4 S BT.  
A Cedar 24" dia., bears S.55°W., 16 lks. mkd. 1/4 S BT.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - Sept. 1954/April 1955 - C.S. File 41/373

-----  
Determined at the record bearing and distance from both original bearing trees.  
At the corner point  
Set an Iron pipe 3 ft. long, 1 1/2" dia., 28" in the ground, mkd. RS33; from which the original bearing trees:  
A D.Fir 28" dia., bears East, 50 lks. mkd. on bark 1/4 SBT  
An I.Cedar 36" dia., bears S.55°W., 16 lks. dist. mkd. on bark 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell and crew - March 14, 1968 - C.S. File 54/36-129

-----  
Found - 1 1/2" Iron pipe at 1/4 corner.  
Orig. 22" now 28" D.Fir, East 33.0 ft., shows good bark scribe, 1/4 S BT  
Orig. 24" now 36" Cedar S.55°W., 10.6 ft., no marks visible.  
Reblazed and rescribed:  
36" Cedar S.55°W., 10.6 ft. mkd. 1/4 S22 CS BT.