

PRIMARY CORNER DESCRIPTION Sec. cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8727-28)

-----  
Set Pine post, 4 ft. long, 4" sq., 22" in the ground for the corner to secs. 14, 15, 22 and 23 marked T32S R7W S14 on NE.; S23 on SE.; S22 on SW.; and S15 on NW., also three notches on S. and two notches on E. angles, from which

- A Laurel 12" dia., bears N.65°E., 59 lks. mkd. T32S R7W S14 BT.
- A Laurel 12" dia., bears S.60°E., 16 lks. mkd. T32S R7W S23 BT.
- A Laurel 10" dia., bears S.40°W., 8 lks. mkd. T32S R7W S22 BT.
- A Laurel 10" dia., bears N.42°W., 25 lks. mkd. T32S R7W S15 BT.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - Sept. 1954/April 1955 - C.S. File 41/373

-----  
Determined at the record bearing and distance from each original bearing tree.  
At the corner point  
Set an Iron pipe 3 ft. long, 2" dia., 28" in the ground mkd. RS33; from which the original bearing trees:

- A Madrona 16" dia., bears N.65°E., 59 lks. dist. with partial scribe marks on decayed old blaze.
- A Madrona 16" dia., bears S.60°E., 16 lks. dist. with partial scribe marks on decayed old blaze.
- A Madrona 12" dia., bears S.40°W., 8 lks. dist. with old blaze decayed.
- A Madrona 11" dia., bears N.42°W., 25 lks. dist. with old blaze decayed.

and new bearing trees:

- A Madrona 12" dia., bears S.85°E., 46 lks. dist. mkd. T32S R7W S23 RS33 BT.
- A Yellow Pine 12" dia., bears S.14°W., 27 lks. dist. mkd. T32S R7W S22 RS33 BT.
- A D.Fir 10" dia., bears N.67°W., 29 lks. dist. mkd. T32S R7W S15 RS33 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - November 1967 - C.S. File 54/36-137

-----  
Found - 2" Iron pipe at section corner.  
12" now 14" Laurel S.87½°E., (Rec. S.85°E.) 30.4 ft., shows bark scribing.  
(Cont. Next Page)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" now 14" Pine S.14°W., 17.8 ft. shows pitched over scribing.  
10" D.Fir now down, N.67°W., 19.1 ft.  
New BTs -5" Chinquapin N.54°E., 35.5 ft., scribed S14 CS BT.  
22" D.Fir N.13°W., 54.1 ft. scribed T32S R7W S15 CS BT.  
This corner lies on top of ridge running NW-SE.