

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 420, survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8729)

Set a Fir post, 4 ft. long, 4" sq., 22" in the ground mkd. ¼ S on W. side, for the ¼ sec. cor, from which
A Fir 14" dia., bears S.58°E., 98 lks. dist., mkd. ¼ S BT.
A Fir 10" dia., bears S.1°W., 84 lks. dist., mkd. ¼ S BT.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - May 1956 - C.S. File 42/143-1

Determined at record bearing and distance from each original bearing tree.
Set an Iron pipe, 3 ft. long, 1½" dia., 28" in the ground, mkd. RS33.
from which the original bearing trees:
The badly decayed remains of a D.Fir stump, bears S.58°E., 98 lks. dist. in which no marks remain.
A sawed D.Fir stump, 22" dia., bears S.1°W., 84 lks. dist. mkd. on bark BT.
and new bearing trees:
A D.Fir 10" dia., bears N.71½°E., 17 lks. dist., mkd. ¼ S14 RS33 BT.
A D.Fir 9" dia., bears N.68½°W., 12 lks. dist., mkd. ¼ S15 RS33 BT.

Fd. OK, DCSO, J.Powell, Nov. 1967, C.S. File 54/36-143