

PRIMARY CORNER DESCRIPTION Sec. cor. for 10, 11, 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8729)

Set a Pine post 4 ft. long, 4" sq., 20" in the ground for the cor. to secs. 10, 11, 14 and 15 marked T32S R7W S11 on NE.; S14 on SE.; S15 on SW.; and S10 on NW. faces, also 4 notches on S. and two on E. angles of same, from which
A Pine 16" dia., bears N.70°E., 152 lks. mkd. T32S R7W S11 BT.
A Pine 40" dia., bears S.45°E., 228 lks. mkd. T32S R7W S14 BT.
A Laurel 10" dia., bears S.38°W., 46 lks. mkd. T32S R7W S15 BT.
A Live Oak 8' dia., bears N.65°W., 94 lks. mkd. T32S R7W S10 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - Nov. 1967 - C.S. File 54/36-142

Found - Orig. 16" now 36" Pine N.70°E., 100.3 ft., opened for scribe "S11 W"
Orig. 40" Pine, now stump hole, S.45°E., 150.5 ft. this hole is approx. S.35°E., 150 ft., no evidence.
Orig. 10" Laurel now rotten hole, S.38°W., 30.4 ft.
Orig. 8" Oak, now broken stump, N.65°W., 62.0 ft.
Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 7 W
S 10 | S 11
S 15 | S 14
1967
New BTs -11" Laurel N.66°E., 29.8 ft. mkd. T32S R7W S11 CSBT
7" Laurel S.50½°W., 8.9 ft. mkd. T32S R7W S15 CS BT
7" D.Fir S.42°E., 28.4 ft. mkd. T32S R7W S14 CS BT.
8" Laurel N.44°W., 14.1 ft. mkd. T32S R7W S10 CS BT

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1199, surveyed July 1984 -(DCSO records Vol. 47 Page(s) 17975)

The Sec. cor., perpetuated and recorded by Powell in 1967, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground, with 1967 brass cap. from which the remains of the original bearing trees:
A Pine 38" dia., bears N.70°E., 152 lks. dist., with fragmentary scribe marks visible on opened blaze.
(Cont. Next Page)

