

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8730)

Set a Fir post, 4 ft. long, 4" sq., 18" in the ground marked 1/4 S on W. side for 1/4 sec. cor., from which
A Laurel 10" dia., bears S.40°E., 39 lks. mkd. 1/4 S BT.
A Fir 12" dia., bears S.50°W., 35 lks. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - Dec. 1967 - C.S. File 54/36-102

Found - Orig. 12" now 30" D.Fir windfall, S.50°W., 23.1 ft. scribe visible, 1/
Orig. Laurel, down, S.40°E., 25.7 ft., down, all but gone.

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 7 W
1/4 S 10 | S 11
1967

New BTs -10" Yew S.68°E., 23.0 ft. mkd. 1/4 S11 CS BT.

14" Fir N.86°W., 25.0 ft. mkd. 1/4 S10 CS BT.

This corner lies 100 ft. North of draw running E & W.