

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8732-33)

-----  
Set a Fir post, 4 ft. long, 22" in ground, 4" sq., mkd. ¼ S on W. side for the ¼ sec. cor., from which  
A Fir 40" dia., bears East, 36 lks. dist. mkd. ¼ S BT.  
A Pine 36" dia., bears N.5°W., 61 lks. dist. mkd. ¼ S BT

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #543, surveyed June, 1964 (DCSO records Vol. 33 Page(s) 13651)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked  
T 32 S R 7 W  
¼  
S 3 | S 2  
1964

from which  
A Fir 6" dia., bears S.23°E., 81 lks. dist., mkd. ¼ S2 BT  
A Fir 6" dia., bears N.45°W., 55 lks. dist., mkd. ¼ S3 BT

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1086, surveyed April/June 1982 - (DCSO records Vol. 46 Page(s) 17570)

-----  
The ¼ sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with 1964 brass cap. from which the remains of a bearing tree mkd. by Beck  
A root hole bears N.45°W., 55 lks. dist., with a down Fir alongside, 6" dia., with fragmentary scribe marks visible on decayed blaze.  
and new bearing trees:  
A Fir 8" dia., bears S.31°W., 49 lks. dist., mkd. X BT.  
A Fir 8" dia., bears N.70½°W., 24 lks. dit. mkd. ¼ S3 BT.  
No suitable trees available within limits in sec. 2.

Mark Heimburger - Crew: Bartt Heichel & Anthony Welch - 2/2018 - C.S. File 65/101-43

-----  
Found - 2½" Brass Cap on 2½" iron pipe set in cut slope of logging skid road from which a:  
13" D.fir stump badly rotten bears S.31°W., 32.0'  
12" D.fir stump badly rotten bears N.70°W., 16.2'  
New BTs- 10" D.fir scribed "¼ S2 Br bears S.71°E., 15.2'  
continued next page

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

10" D.fir scribed "X BT" bears S.9°E., 16.1'  
8" D.fir scribed "¼ S3 BT" bears S.48°W., 18.5'  
5/8"x30" iron rod w/plastic cap marked "LAND MARK  
PLS2287 bears S.74°E., 9.2'

Note - Oregon coordinate reference system, Cottage Grove -  
Canyonville zone, NAD 88-(2011) EPOCH 2010  
Per GIS Observation holding NGS CORS STATIONS  
"RSBG" & "DDSN"  
Lat. N.43°09'04.8999" Long. W.123°37'47.4072"