

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 511100

PRIMARY CORNER DESCRIPTION N. Sec. cor. for 2 and 3 only, T33-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 9039)

-----  
Set a Fir post, 4 ft. long, 4" sq., 2 ft. in the ground, mkd. C C T33S R7W on S.; S2 and 2 notches on E.; S3 and 4 notches on W. and T32S R7W S35 on N. faces for the closing corner between secs. 2 and 3, from which

A Laurel 10" dia., bears S.24°E., 6 lks. dist. mkd. T33S R7W S2 BT.

A Chinquapin 12" dia., bears S.47°W., 12 lks. dist., mkd. T33S R7W S3 BT.

A Chinquapin 5" dia., bears N.45°W., 22 lks. dist., mkd. T32S R7W S35 BT.

Survey by George J. Wenderoth - May 1965 - C.S. File 52/140

Found - Wooden stake at corner.

BLM tag on Madrona tree, S.83°E., 4.3 ft., old BT.

Stake rotted and just standing, BT, dead and rotten

Set Brass cap at corner.

New BTs -16" Chinquapin S.18°48'E., 16.6 ft.

24" Chinquapin S.82°50'E., 28.0 ft.

Fd. OK, DCSO, John Powell, Dec. 18, 1967 C.S. File 54/36-125

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #845, surveyed April/Nov. 1975 (DCSO records Vol. 41 Page(s) 16273-74)

-----  
(25.775 chs.)

The closing cor. of secs. 2 and 3, perpetuated and recorded by Wenderoth in 1965, monumented with an iron pipe, 1¼" dia., firmly set, extending 5" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE R7W 2 3 T33S 1965 DEP LS 5, from which the remains of the original bearing trees:

A Madrone snag, 13" dia., bears S.24°E., 6 lks. dist., with illegible scribe marks visible in negative on overgrowth.

A clump of Chinquapin bears S.47°W., 12 lks. dist.

A Chinquapin 22" dia., bears N.45°W., 22 lks. dist., with healed blaze.

and bearing trees mkd. by Wenderoth

A Chinquapin 22" dia., bears S.83°E., 43½ lks. dist., with scribe marks S2 CS BT visible on partially healed double blaze.

(Cont. Next Page)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 511100

PRIMARY CORNER DESCRIPTION C C for Secs. 2 and 3 only, T33-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Chinquapin 16" dia., bears S.18 3/4°E., 26 lks. dist.,  
with scribe marks S2 CS BT visible on partially healed  
double blaze.

**This point now becomes an amended monument.**

(25.83 chs.)

True point for closing cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in  
the ground, with brass cap marked

T 32 S R 7 W  
S 35  
S 3 | S 2  
T 33 S R 7 W  
C C  
1975

from which the remains of the original bearing trees now bear

A Madrone snag, 13" dia., bears S.13½°E., 11 lks. dist.

A clump of Chinquapin bears S.28°W., 17 lks. dist.

A Chinquapin 22" dia., bears N.58°W., 19½ lks. dist.

and bearing trees mkd. by Wenderoth

A Chinquapin 22" dia., bears S.78°E., 44½ lks. dist.

A Chinquapin 16" dia., bears S.17½°E., 30½ lks. dist.

No suitable tree available in Sec. 3.

Fd. Ok - R. Mason - Oct. 2, 1997 - M 127-64 & CS 65/16-3