

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 540140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 35

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

BLM Dependent resurvey by Stephan L. Barott, Cadastral Surveyor (Forest Service, USDA) under Group #1995, surveyed April/Nov. 2002 - (DCSO records Vol. 54 Page(s) 21171-2)

-----  
Point for the center ¼ sec. cor. of sec. 35, at intersection with the E & W centerline.  
Set a stainless steel post, 28" long, 2½" dia., 27" in the ground, with brass cap mkd.

T 32 S R 7 W  
C ¼ S 35  
2002

from which

A fir, 7" dia., bears N.9½°E., 10.6 ft., mkd. C ¼ S35 BT.  
A fir, 8" dia., bears S.5¾°E., 3.2 ft., mkd. C ¼ S35 BT.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.