

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8728)

Set a Laurel post, 4 ft. long, 4" sq., 22" in the ground mkd. 1/4 S on N. side for the 1/4 sec. cor., from which
A Fir 14" dia., bears N.50°E., 22 lks. dist. mkd. 1/4 S BT.
A Laurel 16" dia., bears S.60°E., 13 lks. dist. mkd. 1/4 SBT

Douglas Co. Surveyors Office - V.R. Tracy, Jack Heritage, V. Perron, crew - March 10, 1970 - C.S. File 54/36-107

Found - Orig. 14" now 26" Fir, alive, N.50°E., 14.5 ft., fragmentary bark scribe and an axe notch below blaze. We re-scribe 1/4 S14 CS BT
Orig. 16" now 22" Laurel, alive, S.60°E., 8.6 ft., previously opened, blaze decayed. Rescribe "1/4 S23 CS BT"

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 7 W
1/4 S 14
S 23
1970

New BT - 36" Pine S.41°W., 28.7 ft. mkd. 1/4 S23 CS BT.
This corner lies 60 ft. North of ridge, sloping westerly.

Cor. Fd. and used in BLM resurvey by Popken, under Group #884, surveyed Sept 1975/June 1976 (DCSO records, Vol. 37 Page 15320)

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Dec. 2018 - (DCSO records Vol. 59 Page(s) 23773-4)

The 1/4 sec. cor. of secs. 14 and 23, reported by Popken and Carlson in 1975-76, monumented with an iron post, 1 1/2" dia., (Record 1" dia.) firmly set, projecting 7" above the ground, with brass cap (properly) mkd.

from which bearing trees reported by Popken and Carlson
A fir, 34" dia., bears N.50°E., 15.2 ft., with a healed blaze. (Original)

A ponderosa pine, 38" dia., bears S.38 3/4°W., 28.3 ft., with a healed double blaze. (Record, S.37 1/2°W., 29.0 ft.)

NAD 1983 (2011)

Latitude: 42°46'54.73" N. Longitude: 123°29'45.08" W.