

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8730)

-----  
Set a Chinquapin post, 4 ft. long, 4" sq., 22" in the ground, marked ¼ S on N. side for the ¼ sec. cor., from which  
A Fir 36" dia., bears N.36°E., 95 lks. mkd. ¼ S BT.  
A Pine 40" dia., bears S.50°E., 30 lks. mkd. ¼ S BT.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1199, surveyed July 1984 -(DCSO records Vol. 47 Page(s) 17974)

-----  
The ¼ sec. cor., determined from the remains of the original bearing trees:

- A Fir root crown, size indeterminate, bears N.36°E., 95 lks. dist., no marks visible.
- A sawed Pine stump, 50" dia., bears S.50°E., 30 lks. dist., with axe marks visible.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked T 32 S R 7 W

¼ S 11  
S 14  
1984

from which new bearing trees:

- A Fir 6" dia., bears N.51°E., 9 lks. dist., mkd. ¼ S11 BT.
- A Fir 6" dia., bears S.69°W., 26½ lks. dist. mkd. ¼ S14 BT

Daniel Baker - For: Weyerhaeuser Co. - 12/2016 - M173-1

-----  
Found - 3¼" BLM brass cap "1984"  
10" fir, N.50°E., 6.0' to center, 1984 BLM BT (Rec. N.51°E., 9 lks)  
43" pine stump, S.50°E., 19.7' to center, orig. BT (rec. S.50°E., 30 lks)  
11" fir, S.70°W., 17.6' to center, 1984 BLM BT (Rec. S.69°W., 26½ lks)  
Marked - 14" fir, S.69°E., 13.5' to nail side/center, scribed "¼ S14 BT"  
13" fir, N.58°W., 27.7' to nail side/center, scribed "¼ S11 BT"  
Note - 5 ft. metal post alongside corner.